

Calla



Specifikationer

Udformning:	Formstøbt polycarbonat
Afskærmning:	Opal
Spænding:	220-240V ~ 50-60 Hz
Driver:	CC & CC-DA
Levetid:	50.000 timer fejlrate max. 10%
Flimrer:	≤ 4 %
Montage:	Påbygget og væghængt
Lysnedgang:	L80/B10>50.000 timer v/Ta 25°C
SDCM:	MacAdam 3
Lysudbytte:	<92lm/Watt
Farve:	Hvid
Producentgaranti:	5 år
Styringstilvalg:	Ultralydssensor (On/Off)
Lysfarve:	3000K, 4000K

Wattage	Dimensioner			Vægt	Lysfarve	Ra-værdi	Lumen
	A	B	H				
12W	350	-	128	1,7	4000K	>80	1100 lm
19W	350	-	128	1,7	4000K	>80	1800 lm
24W	350	-	128	1,7	4000K	>80	2200 lm
12W	350	-	128	1,7	3000K	>80	1050 lm
19W	350	-	128	1,7	3000K	>80	1750 lm
24W	350	-	128	1,7	3000K	>80	2150 lm


Yderligere informationer

Godkendt til fællesadgangsveje

IK Klasse: IK10



Tekniske mål og tegninger



Overensstemmelser



Photometrisk data

