



## Specifikationer

Udformning:	Hvidlakeret stålplade
Afskærmning:	Mikroprismatisk
Spænding:	220-240V ~ 50-60 Hz
Driver:	On/Off, 1-10V, DSI & DALI
Montage:	Indbygget eller påbygget
Lysnedgang:	L80/B10>50.000 timer v/Ta 25°
SDCM:	MacAdam 3
Lysudbytte:	<132 lm/Watt
Farve:	Pulverlakeret hvid
Producentgaranti:	5 år
Styringstilvalg:	ILD og ESA
Lysfarve:	3000K, 4000K

Wattage	Dimensioner			Vægt kg	Lysfarve	Ra-værdi
	A	B	H			
18W	595	595	80	3,6	4000K	>80
21W	595	595	80	3,6	4000K	>80
25W	595	595	80	3,6	4000K	>80
29W	595	595	80	3,6	4000K	>80
18W	595	595	80	3,6	3000K	>80
21W	595	595	80	3,6	3000K	>80
25W	595	595	80	3,6	3000K	>80
29W	595	595	80	3,6	3000K	>80


## Yderligere informationer

Mulighed for UGR<19 med mikroprismatisk afskærmning

Mulighed for Ra 90



## Tekniske mål og tegninger



## Overensstemmelser



## Photometrisk data

